

# CATALOG

**A D A** INSTRUMENTS

Laser tools

Surveying tools

Inspection and diagnostic tools

Angle meters and levels

Measuring tapes and measuring wheels

Accessories





ADAINSTRUMENTS.COM



**ADA INSTRUMENTS – is a company specializing in the design and manufacturing of measuring equipment.**

The main direction of ADA Instruments is the development and production of laser instruments:

- laser distance meters
- line lasers
- accessories and tripods

Additionally the range of products includes more than 8 types of equipment:

- pyrometers
- auto levels
- theodolites
- inspection and diagnostic tools
- measuring tapes and measuring wheels
- digital and spirit levels
- angle meters
- ground drills

Main advantages of the equipment:

- User-oriented approach
- High quality of the products
- Integrated design
- Maintenance service








# ARMO 2D

Line laser



ADA ARMO 2D – is a compact self-leveling line laser with the universal mount. It projects one horizontal and one vertical lines. ADA ARMO 2D laser lines are suitable for most home-repair marking jobs: laying tiles in a small room, installing furniture, hanging shelves, wallpapering, installing cornices, etc.

|  |                        |
|--|------------------------|
| Working range without/with receiver, m | 20/40                  |
| Accuracy, m/mm                         | ±0,3                   |
| Laser projection                       | 2 lines                |
| Dust/water projection                  | IP 54                  |
| Power supply                           | 2 batteries AA / 1.5 V |



Complete set



**PROFESSIONAL EDITION**  
ART. A00574


device, batteries, tripod,  
charger, operating manual



## Line laser

ADA ARMO 2D GREEN is a compact line laser with green beam that projects one horizontal and one vertical lines. It is used almost in all applications concerning repair: partitions, laying of communication systems, installation of doors, windows, furniture and so on.

|  |                        |
|--|------------------------|
| Working range without/with receiver, m | 40/70                  |
| Accuracy, m/mm                         | ±0,3                   |
| Laser projection                       | 2 lines                |
| Dust/water projection                  | IP 54                  |
| Power supply                           | 2 batteries AA / 1.5 V |



## ARMO 2D GREEN



## Complete set




### PROFESSIONAL EDITION ART. A00575

device, batteries, charger, tripod, operating manual

## Line laser

ADA ARMO MINI is a compact self-leveling line laser that projects one horizontal and one vertical lines. It is used almost in all applications concerning repair: partitions, laying of communication systems, installation of doors, windows, furniture and so on..

|                       |                        |
|-----------------------|------------------------|
| Working range, m      | 10                     |
| Accuracy, m/mm        | ±0,3                   |
| Laser projection      | 2 lines                |
| Dust/water projection | IP 54                  |
| Power supply          | 2 batteries AA / 1.5 V |



## ARMO MINI



ART. A00582


### COMPLETE SET:

device, batteries, operating manual

## Line laser

ADA ARMO MINI GREEN is a compact self-leveling line laser with green laser beam that projects one horizontal and one vertical lines. It's perfect for dedicated DIY homeowners, and can be used for anything from fixing shelving to laying floor tiles, hanging wallpapers, and so much more and more. ADA ARMO MINI GREEN is a perfect tool for those who likes to do the repair with their own hands.

|                       |                        |
|-----------------------|------------------------|
| Working range, m      | 20                     |
| Accuracy, m/mm        | ±0,3                   |
| Laser projection      | 2 lines                |
| Dust/water projection | IP 54                  |
| Power supply          | 2 batteries AA / 1.5 V |



## ARMO MINI GREEN



ART. A00590

### COMPLETE SET:

device, batteries, operating manual



# CUBE MINI

---

Line laser






## Line laser

ADA CUBE MINI is the most compact self-leveling line laser that is used almost in all applications concerning repair: partitions, laying of communication systems, installation of doors, windows, furniture and so on. Due to the intersecting lines (angle between laser planes is 90°) it is possible to make fast marking when setting materials and constructions..

|                       |                        |
|-----------------------|------------------------|
| Working range, m      | 20                     |
| Accuracy, m/mm        | ±0,2                   |
| Laser projection      | 2 lines                |
| Dust/water projection | IP 54                  |
| Power supply          | 2 batteries AA / 1.5 V |



## CUBE MINI



### Complete set



#### **BASIC EDITION** ART. A00461

device, battery, plastic box, operating manual




#### **PROFESSIONAL EDITION** ART. A00462

device, bag, batteries, tripod, plastic box, operating manual

## Line laser

ADA CUBE MINI Green is the most compact self-leveling line laser. It projects one horizontal and one vertical lines. Laser lines ada cube mini green are used almost in all applications concerning repair: partitions, laying of communication systems, installation of doors, windows, furniture and so on. Intersecting planes at an angle of 90°. Due to the intersecting lines (angle between laser planes is 90°) it is possible to make fast marking when setting materials and constructions.

|                       |                        |
|-----------------------|------------------------|
| Working range, m      | 20                     |
| Accuracy, m/mm        | ±0,2                   |
| Laser projection      | 2 lines                |
| Dust/water projection | IP 54                  |
| Power supply          | 2 batteries AA / 1.5 V |



## CUBE MINI GREEN



### Complete set



#### **BASIC EDITION** ART. A00496

device, battery, plastic box, operating manual



#### **PROFESSIONAL EDITION** ART. A00529

device, bag, batteries, tripod, plastic box, operating manual



# CUBE

---

## Line laser


ADA CUBE is the most compact professional line laser. Minimal sizes. Convenient housing in the form of cube. The size of the edge is only 6.5 cm. It's ideal tool for accurate marking in repair, construction. With the help of ADA CUBE you can do any work: to hang a shelf or a picture on the wall, to hang wallpapers, to place conduit for electric wiring, to set guides for suspended ceiling and so on.





## Line laser

|                       |                         |
|-----------------------|-------------------------|
| Working range, m      | 20                      |
| Accuracy, m/mm        | ±0,2                    |
| Laser projection      | 2 lines                 |
| Dust/water projection | IP 54                   |
| Power supply          | 3 batteries AAA / 1.5 V |



## CUBE



### Complete set



#### BASIC EDITION

ART. A00341

device, battery, plastic box, operating manual



#### PROFESSIONAL EDITION

ART. A00343

device, bag, batteries, tripod, plastic box, operating manual



#### ULTIMATE EDITION

ART. A00344

device, clamp, laser glasses, case, tripod, batteries, operating manual

Thread 1/4» on the bottom of the instrument allows to set it on the tripod or universal mount. Switching on and unblocking with one button. Separate laser emitters are used to project laser lines. It allows to get clear and bright laser lines. Pendulum suspension goes fast into vertical position. Maximum deviation from vertical axis is 3°. Acoustic alarm is given when the instrument is out of self-leveling range.

The instrument can come with universal mount (for complete set HOME) or elevating tripod (for complete set PROFESSIONAL). Universal mount is made in the form of reliable steel clamp with rotary screw for surface attachment at any angle. Clamps of universal mount have soft cover. That's why they don't leave any traces on the surface.








# CUBE 3D

Line laser

Laser level ADA CUBE 360 is the measuring gauge. Its functions can be estimated both by professionals and by private users. Special projector allows projection of horizontal ray up to 360°. It suits for building or repair, for leveling in the process of laying ceramic tiles or other coverage, papering walls, laying curbs etc.



|  |                         |
|--|-------------------------|
| Working range without/with receiver, m | 20/40                   |
| Accuracy, m/mm                         | ±0,2                    |
| Laser projection                       | 3 lines                 |
| Dust/water projection                  | IP 54                   |
| Power supply                           | 3 batteries AAA / 1.5 V |



## Complete set



### BASIC EDITION ART. A00382

device, battery, plastic box, operating manual



### PROFESSIONAL EDITION ART. A00384

device, bag, batteries, tripod, plastic box, operating manual



### ULTIMATE EDITION ART. A00385


device, clamp, laser glasses, case, tripod, batteries, plastic box, operating manual



## Line laser

ADA CUBE 3D GREEN is the most compact line laser with two vertical and one horizontal lines. With the help of ADA Cube you can do all marking jobs: to hang a shelf or picture on the wall, to hang wallpapers, to place conduit for electric wiring, to set guides for suspended ceiling and so on. Due to the vertical lines that are intersected at the angle of 90° you can easily plan the division of the room, make partitions, lay floor tiles and so on. Laser lines will show the position of future walls. Change the position of the level to value the dimensions of planned room.

|  |                         |
|--|-------------------------|
| Working range without/with receiver, m | 40/70                   |
| Accuracy, m/mm                         | ±0,2                    |
| Laser projection                       | 3 lines                 |
| Dust/water projection                  | IP 54                   |
| Power supply                           | 3 batteries AAA / 1.5 V |



## CUBE 3D GREEN



## Complete set



### PROFESSIONAL EDITION ART. A00545

device, bag, batteries, tripod, plastic box, operating manual

Turning on and deblocking is performed with the click of the button. The pendulum makes fast alignment into vertical position. Maximum deviation from the vertical axis makes up 3°. In case of deviation the acoustic alarm activates. Thread 1/4 in the bottom of the gauge allows to set on the tripod or multipurpose fixing.








# CUBE 360

Line laser

Line laser ADA CUBE 360 is the modern gauge. Its functions can be appreciated both by professionals and by private users. Special projector allows projection of horizontal ray up to 360°. It suits for building or repair, for leveling in the process of laying ceramic tiles or other coverage, papering walls, laying curbs etc.



|  |                        |
|--|------------------------|
| Working range without/with receiver, m | 20/70                  |
| Accuracy, m/mm                         | ±0,3                   |
| Laser projection                       | 2 lines (1 line 360°)  |
| Dust/water projection                  | IP 54                  |
| Power supply                           | 3 batteries AA / 1.5 V |



## Complete set



### BASIC EDITION ART. A00443

device, battery,  
operating manual



### HOME EDITION ART. A00444

device, wall mount, bag, batteries,  
magnet target, laser glasses, operating  
manual



### PROFESSIONAL EDITION ART. A00445

device, bag, batteries, magnet target,  
tripod, operating manual




### ULTIMATE EDITION ART. A00446

device, bag, wall mount, laser glasses,  
case, tripod, batteries, ADA MAGNETIC  
LIFT, magnet target, operating manual



## Line laser

|  |                        |
|--|------------------------|
| Working range without/with receiver, m | 40/70                  |
| Accuracy, m/mm                         | ±0,3                   |
| Laser projection                       | 2 lines (1 line 360°)  |
| Dust/water projection                  | IP 54                  |
| Power supply                           | 3 batteries AA / 1.5 V |



# CUBE 360 GREEN



## Complete set



### PROFESSIONAL EDITION ART. A00535

device, bag, charger, Li-on battery, tripod, magnet target, operating manual



### ULTIMATE EDITION ART. A00470

device, bag, charger, Li-on battery, tripod, magnet target, operating manual, ADA MAGNETIC LIFT

Line laser ADA CUBE 360 Green is the instrument with green laser beam. Green beam has good visibility in bright light. Bright laser line helps to make fast and accurate marking without the use of additional equipment.

Special emitter projects 360° horizontal beam. It is the ideal tool during construction and repair works when paving tile laying or other coating, wallpapering and so on.

Automatic self-leveling. Instrument has high accuracy.





# CUBE 360-2V

Line laser



ADA CUBE 360-2V is a compact line laser that projects 3 laser planes: 1 horizontal 360° and 2 vertical planes. Due to the special emitter the horizontal and vertical beams are projected by 360°. It's ideal tool for accurate marking in repair, construction both inside and outside.


|  |                        |
|--|------------------------|
| Working range without/with receiver, m | 20/70                  |
| Accuracy, m/mm                         | ±0,3                   |
| Laser projection                       | 3 lines (1 line 360°)  |
| Dust/water projection                  | IP 54                  |
| Power supply                           | 3 batteries AA / 1.5 V |

## Complete set



## PROFESSIONAL EDITION ART. A00570

device, tripod, battery,  
magnet target, operating manual





## Line laser

ADA CUBE 360-2V GREEN is a compact line laser that projects 3 laser planes: 1 horizontal 360° and 2 vertical planes. The color of the laser beam is green. Due to the special emitter the horizontal and vertical beams are projected by 360°. 120 degree vertical scanning. It's ideal tool for accurate marking in repair, construction both inside and outside.

|  |                        |
|--|------------------------|
| Working range without/with receiver, m | 40/70                  |
| Accuracy, m/mm                         | ±0,3                   |
| Laser projection                       | 3 lines (1 line 360°)  |
| Dust/water projection                  | IP 54                  |
| Power supply                           | 3 batteries AA / 1.5 V |


## Complete set



### PROFESSIONAL EDITION ART. A00571

device, tripod, Li-on battery,  
charger, magnet target, wire, operating  
manual

# CUBE 360-2V GREEN



Bright green beam. Green laser emitter is a main advantage of ADA CUBE 360 2V GREEN.

Green beam is ideal for laser marking in bright light. Green laser beam provides the best visibility in comparison with red beam under the same working conditions.





# CUBE 2-360

---

## Line laser


Line laser ADA CUBE 2-360 is the compact device intended for creating two closed laser lines. Special projector allows projection of horizontal ray up to 360°. One line is vertical, the other is horizontal. It suits for building or repair, for leveling in the process of laying ceramic tiles or other coverage, papering or leveling walls, installation of suspended structures or floating ceilings etc.





## Line laser

|  |                        |
|--|------------------------|
| Working range without/with receiver, m | 20/70                  |
| Accuracy, m/mm                         | ±0,3                   |
| Laser projection                       | 2 lines 360°           |
| Dust/water projection                  | IP 54                  |
| Power supply                           | 3 batteries AA / 1.5 V |



## CUBE 2-360



### Complete set



#### BASIC EDITION ART. A00447

device, battery, operating manual



#### HOME EDITION ART. A00448

device, wall mount, bag, batteries, magnet target, laser glasses, operating manual



#### PROFESSIONAL EDITION ART. A00449

device, bag, batteries, magnet target, tripod, operating manual




#### ULTIMATE EDITION ART. A00450

device, bag, wall mount, laser glasses, case, tripod, batteries, magnet target, operating manual, ADA MAGNETIC LIFT

## Line laser

ADA CUBE 2-360 Green is the tool with green laser beam. Green beam has good visibility in bright light. Special emitter projects 360° horizontal beam. It is ideal device during construction and repair works when paving tile laying or other coating, wallpapering, wall leveling, installation of a suspended constructions and ceilings and so on.

|  |                        |
|--|------------------------|
| Working range without/with receiver, m | 40/70                  |
| Accuracy, m/mm                         | ±0,3                   |
| Laser projection                       | 2 lines 360°           |
| Dust/water projection                  | IP 54                  |
| Power supply                           | 3 batteries AA / 1.5 V |



## CUBE 2-360 GREEN



### Complete set



#### PROFESSIONAL EDITION ART. A00534

device, tripod, bag, Li-on battery, charger, wire USB (type-C) DC 5V, target, operating manual



#### ULTIMATE EDITION ART. A00471

device, bag, wall mount, laser glasses, case, tripod, batteries, magnet target, ADA MAGNETIC LIFT, wire USB (type-C) DC 5V, operating manual



# CUBE 3-360

---

## Line laser

Line laser ADA CUBE 3-360 is the device with maximum possibilities for today. Laser level projects three planes 360°: one horizontal and two vertical lines. This is the best laser projection. It's ideal device for wall leveling.






Line laser ADA CUBE 3-360 is the most compact laser line level that builds 3x360° laser planes. Horizontal and vertical beams are projected by 360° due to the special emitter. Three mutually perpendicular laser planes allow you to easily mark out any type of surface area. Ideal for construction or repair work both for interior and exterior applications.

# CUBE 3-360

|  |                                   |
|--|-----------------------------------|
| Working range without/with receiver, m | 20/70                             |
| Accuracy, m/mm                         | ±0,3                              |
| Laser projection                       | 3 lines 360°                      |
| Dust/water projection                  | IP 54                             |
| Power supply                           | 3 batteries AA / 1.5 V or charger |



## Complete set



**BASIC EDITION**  
ART. A00559

device, batteries, operating manual



**HOME EDITION**  
ART. A00565

device, mount, bag, batteries, laser glasses, magnet target, operating manual, ADA BASE



**PROFESSIONAL EDITION**  
ART. A00572

device, tripod, bag, battery, magnet target, operating manual



**ULTIMATE EDITION**  
ART. A00568

device, mount, laser glasses, case, tripod, Li-ion battery, ADA BASE, charger, magnet target, wire, operating manual








Line laser ADA CUBE3-360 Green is the tool with three bright green laser beams 360°. It is ideal device during construction and repair works when paving tile laying or other coating, wallpapering, wall leveling, installation of a suspended constructions and ceilings and so on. Use Li-on battery for continuous operation.

# CUBE 3-360 GREEN

Line laser



|  |                                   |
|--|-----------------------------------|
| Working range without/with receiver, m | 40/70                             |
| Accuracy, m/mm                         | ±0,3                              |
| Laser projection                       | 3 lines 360°                      |
| Dust/water projection                  | IP 54                             |
| Power supply                           | 3 batteries AA / 1.5 V or charger |



## Complete set



**BASIC EDITION**  
ART. A00560

device, Li-on battery, charger, wire, operating manual



**HOME EDITION**  
ART. A00566

device, mount, bag, Li-on battery, charger, wire, magnet target, ADA BASE, operating manual



**PROFESSIONAL EDITION**  
ART. A00573

device, tripod, bag, Li-on battery, charger, wire, magnet target, operating manual



**ULTIMATE EDITION**  
ART. A00569


device, mount, laser glasses, case, tripod, Li-on battery, wire, charger, magnet target, ADA BASE, operating manual



## Line laser

ADA LASERTANK 4-360 GREEN – is a line laser level with 4 bright green laser lines: 2 vertical and 2 horizontal. All laser lines – 360°. In tilt mode, you can set the tool at any angle. There is a receiver mode to work in bright light, on the street. Remote control for turning on and selecting lines. Powered by a powerful lithium battery.

|  |                |
|--|----------------|
| Working range without/with receiver, m | 40/70          |
| Accuracy, m/mm                         | ±0,3           |
| Laser projection                       | 4 lines 360°   |
| Tripod thread                          | 2x1/4"         |
| Power supply                           | Li-ion battery |



# LASERTANK 4-360 GREEN



## Complete set



### BASIC EDITION ART. A00693

device, Li-on battery, charger, case, remote control, operating manual




### ULTIMATE EDITION ART. A00694

device, ADA BASE, charger, remote control, tripod, Li-on battery, target, case, operating manual

## Line laser

ADA LASERTANK 3-360 GREEN – is a line laser with 3 bright green laser lines 360°. In tilt mode, you can set the tool at any angle. There is a receiver mode to work in bright light, on the street. Remote control for turning on and selecting lines. Powered by a powerful lithium battery.

|  |                |
|--|----------------|
| Working range without/with receiver, m | 40/70          |
| Accuracy, m/mm                         | ±0,3           |
| Laser projection                       | 3 lines 360°   |
| Tripod thread                          | 2x1/4"         |
| Power supply                           | Li-ion battery |



# LASERTANK 3-360 GREEN



## Complete set



### BASIC EDITION ART. A00695

device, Li-on battery, charger, case, remote control, operating manual




# 2D BASIC LEVEL



## Line laser

Application areas of the line laser ADA 2D Basic Level: all works in leveling, furniture assembling, tiles laying, wallpaper hanging, equipment mounting. A high-quality tool for repairs and construction with manifold possibilities

|  |                        |
|--|------------------------|
| Working range without/with receiver, m | 20/40                  |
| Accuracy, m/mm                         | ±0,2                   |
| Laser projection                       | 2 lines                |
| Dust/water projection                  | IP 54                  |
| Power supply                           | 3 batteries AA / 1.5 V |



## 2D BASIC LEVEL ART. A00239


Line laser, laser target, laser glasses, soft carrying case, battery, instruction manual

# 3D LINER 2V /4V GREEN

## Line laser

Line laser ADA 3D LINER 2V GREEN – is an accurate line laser that is used for indoor/outdoor operation. ADA 3D LINER 2V GREEN projects bright green laser lines: 2 vertical lines (2V), 1 horizontal (H) line and plumb down (D). ADA 3D LINER 2V GREEN is distinguished by its green laser beam. Green laser beam provides the best visibility in comparison with red beam under the same working conditions.

|  |   |
|--|---|
| Working range without/with receiver, m | 40/70                                   |
| Accuracy, m/mm                         | ±0,2                                    |
| Laser projection                       | 1H 2V 1D                                |
| Dust/water projection                  | IP 54                                   |
| Power supply                           | 4 batteries AA / 1.5 V / Li-ion battery |



## Complete set

## 3D LINER 2V GREEN / 3D LINER 4V GREEN ART. A00532                      ART. A00531

line laser, case for transportation, operating manual, laser glasses, Li-On battery, charger, adapter for Li-On battery, screw-extender, magnet target






Line laser ADA PROLINER 2V / 4V – is a line laser for professional usage in the construction and repair. It is ideal instrument during construction and repair works when paving tile laying or other coating, wallpapering and so on. Line laser projects horizontal laser line in the sector 120°. There are perpendicular planes when switching on vertical lines (depends on the model (2V/4V)).




# PROLINER 2V / 4V

Line laser

|  |   |
|--|---|
| Working range without/with receiver, m | 20/70   |
| Accuracy, m/mm                         | ±0,2  |
| Laser projection                       | 3 lines (2V) / 5 lines (4V) /<br>1 plumb down |
| Dust/water projection                  | IP 54   |
| Power supply                           | Li-Ion battery, 3.7 V /<br>4xAA, 1,5V         |



2V



4V



## Complete set



### PROLINER 2V / 4V ART. A00472 / ART. A00474

device, target, screw-extender 5/8, laser glasses, batteries, battery holder, case, operating manual



### PROLINER 4V SET ART. A00476

device, target, laser glasses, batteries, battery holder, Li-on battery, charger, case, tripod, operating manual



ADA ULTRALiner 360 2V / 3V / 4V is a line laser for professional usage in the construction and repair. Special emitter projects 360° horizontal beam. Emitters project additionally perpendicular vertical planes. It is ideal instrument during construction and repair works when paving tile laying or other coating, wallpapering and so on.




# ULTRALINER 360 2V / 4V


Line laser



|  |  |
|--|--|
| Working range without/with receiver, m | 20/70  |
| Accuracy, m/mm                         | ±0,2   |
| Laser projection                       | 1 line 360° / 2 lines (2V) / 4 lines (4V) / 1 plumb down |
| Dust/water projection                  | IP 54  |
| Power supply                           | Li-Ion battery, 3,7 V / 4xAA, 1,5Vr                      |



2V



4V

Complete set



## ULTRALINER 360 2V / 4V ART. A00467 / ART. A00469

device, screw-extender 5/8, target, laser glasses, batteries, battery holder, case, operating manual



## ULTRALINER 360 4V SET ART. A00477


device, target, laser glasses, batteries, battery holder, Li-ion battery, charger, case, operating manual



## Line laser

ADA ULTRALiner 360 4V Green – is a professional line laser with bright green laser beam. Special emitter projects 360° horizontal beam. Emitters project additionally perpendicular vertical planes. It is ideal instrument during construction and repair works when paving tile laying or other coating, wallpapering and so on.

|  |                                       |
|--|---------------------------------------|
| Working range without/with receiver, m | 40/70                                 |
| Accuracy, m/mm                         | ±0,3                                  |
| Laser projection                       | 1 line 360°/4 lines (4V)/1 plumb down |
| Dust/water projection                  | IP 54                                 |
| Power supply                           | Li-Ion battery, 3,7 V / 4xAA, 1,5V    |



# ULTRALINER 360 4V GREEN



## Complete set



### ULTRALINER 360 4V GREEN ART. A00540

device, screw-extender 5/8,  
target, laser glasses, Li-Ion  
battery, charger, battery holder,  
case, operating manual



### ULTRALINER 360 4V GREEN SET ART. A00497

device, target, laser glasses, Li-Ion battery, 3  
additional sections for tripod, battery holder,  
tripod, case, charger, operating manual

Line laser projects 360° horizontal line. There is no need to rotate the instrument when making horizontal marking. Horizontal beam will be along the perimeter. There are four laser crosses when switching on vertical lines. It is possible to switch off laser lines one-by-one. Just select the line that you need for a work. Laser plumb down helps to detect the dot on the floor.





# 6D SERVOLINER

Line laser




ADA 6D Servoliner is a professional line laser for construction and repair work. ADA 6D Servoliner is a tool with rotary base and combined laser scan: circle horizontal plane 360°, laser plumb down (dot), perpendicular vertical planes. Due to this, the tool has maximum functionality and is suitable for all types of marking work. ADA 6D Servoliner projects circle horizontal laser line 360°. It can be placed in any place. A laser dot on a horizontal line will allow you to mark out at long distances when the line is not visible. For vertical marking, you can turn on the vertical laser lines one by one.

|  |   |
|--|---|
| Working range without/with receiver, m | 20/70   |
| Accuracy, m/mm                         | ±0,1  |
| Laser projection                       | 5 lines (1 line 360°)/1 plumb down            |
| Dust/water projection                  | IP 54   |
| Power supply                           | Li-Ion battery, 12.6 V / 8xAA, 1.5V / charger |

## ART. A00621

### COMPLETE SET:

device, power supply, rechargeable battery, adapter, laser glasses, target, case, operating manual





## Line laser

ADA 6D Servoliner GREEN is a professional line laser for construction and repair work. ADA 6D Servoliner GREEN is a tool with rotary base and combined laser scan: circle horizontal plane 360°, laser plumb down (dot), perpendicular vertical planes. Due to this, the tool has maximum functionality and is suitable for all types of marking work. ADA 6D Servoliner GREEN is distinguished by its green laser emitter. Green beam is ideal for marking under bright light. Green laser beam is much better visible than red under the same conditions.


|  |   |
|--|---|
| Working range without/with receiver, m | 40/70   |
| Accuracy, m/mm                         | ±0,1  |
| Laser projection                       | 5 lines (1 line 360°) / 1 plumb down          |
| Dust/water projection                  | IP 54   |
| Power supply                           | Li-Ion battery, 12.6 V / 8xAA, 1.5V / charger |



ART. A00622

### COMPLETE SET:

device, power supply, rechargeable batteries, adapter, laser glasses, target, case, operating manual



# 6D SERVOLINER GREEN



It can be placed in any place. A laser dot on a horizontal line will allow you to mark out at long distances when the line is not visible. For vertical marking, you can turn on the vertical laser lines one by one. With the help of laser plumb down it is possible to set ADA 6D Servoliner GREEN on initial dot on the floor.

The most advanced servo control system allows you to work with the highest precision not exceeding an error of ± 1 millimeter per 10 meters. With the help of servo drives, by turning on a special mode, you can set the required slope of the laser lines.





# ROTARY 500 HV SERVO

Rotating laser level





## Rotating laser level

Laser level ADA ROTARY 500 HV Servo is equipped with electronic copensator on servodrives. The tool stops operation after unexpected shock during self-leveling. The device starts leveling with the help of servodrives and resumes the operation.

|                       |   |
|-----------------------|---|
| Working range, m      | 400 m (with receiver)                     |
| Accuracy, m/mm        | ±0,15                                     |
| Laser projection      | 1H (360°) or 1V (360°)                    |
| Dust/water projection | IP 54                                     |
| Power supply          | 4 x AA (rechargeable battery) / 1.2 B     |
| Self-leveling mode    | Horizontal automatic / Vertical automatic |

### COMPLETE SET:

device, receiver, receiver mount, remote control, laser target, laser glasses, rechargeable batteries, charger, case, operating manual

## ROTARY 400 HV SERVO



ART. A00458\_2020

## Rotating laser level

Laser level DA ROTARY 500 HV-G Servo is equipped with electronic copensator on servodrives. Automatic self-leveling. It is distinguished by its bright green beam.

|                       |   |
|-----------------------|---|
| Working range, m      | 400 m (with receiver)                     |
| Accuracy, m/mm        | ±0,15                                     |
| Laser projection      | 1H (360°) or 1V (360°)                    |
| Dust/water projection | IP 54                                     |
| Power supply          | 4 x AA (rechargeable battery) / 1.2 B     |
| Self-leveling mode    | Horizontal automatic / Vertical automatic |

### COMPLETE SET:

device, power supply, rechargeable batteries, adapter, laser glasses, target, case, operating manual

## ROTARY 400 HV-G SERVO



ART. A00584

ADA ROTARY 400 HV-G Servo will be perfectly suitable for both horizontal and vertical marking in private construction and during finishing works; for installing the utility lines, floors and walls marking, installation of ceiling and ventilation systems, when performing land planning, marking curvilinear surfaces, carrying out finishing works, furnishing of entrances and exits under slope and so on.





# ROTARY 500 HV SERVO



ART. A00578

## Rotating laser level

ADA ROTARY 500 HV Servo will be perfectly suitable for both horizontal and vertical marking in private construction and during finishing works; for installing the utility lines, floors and walls marking, installation of ceiling and ventilation systems, when performing land planning, marking curvilinear surfaces, carrying out finishing works, furnishing of entrances and exits under slope and so on.

|                       |   |
|-----------------------|---|
| Working range, m      | 500 m (with receiver)                     |
| Accuracy, m/mm        | ±0,15                                     |
| Laser projection      | 1 line 360°                               |
| Dust/water projection | IP 54                                     |
| Power supply          | 4 x AA (rechargeable battery) / 1.2 B     |
| Self-leveling mode    | Horizontal automatic / Vertical automatic |

### COMPLETE SET:

device, receiver, receiver mount, remote control, laser target, laser glasses, rechargeable batteries, charger, case, operating manual

# ROTARY 500 HV-G SERVO



ART. A00579

## Rotating laser level

|                       |   |
|-----------------------|---|
| Working range, m      | 500 m (with receiver)                     |
| Accuracy, m/mm        | ±0,15                                     |
| Laser projection      | 1 line 360°                               |
| Dust/water projection | IP 54                                     |
| Power supply          | 4 x AA (rechargeable battery) / 1.2 B     |
| Self-leveling mode    | Horizontal automatic / Vertical automatic |

### COMPLETE SET:

device, receiver, receiver mount, remote control, laser target, laser glasses, rechargeable batteries, charger, case, operating manual



ADA INSTRUMENTS  
**ROTARY**



# ROTARY 500 HV-G SERVO

## Rotating laser level

ADA ROTARY 500 HV-G Servo will be perfectly suitable for both horizontal and vertical marking in private construction and during finishing works; for installing the utility lines, floors and walls marking, installation of ceiling and ventilation systems, when performing land planning, marking curvilinear surfaces, carrying out finishing works, furnishing of entrances and exits under slope and so on.





# COSMO MINI

Laser distance meter





## Laser distance meter

Laser distance meter ADA COSMO MICRO 25 is the most compact and convenient model of the laser distance meter COSMO series. It has minimum quantity of functions for the measurements. It is used for distance measurements up to 25 m. Measurement error is  $\pm 3,0$  mm. If you notice that the error exceeds the factory settings, then you can make the calibration by yourself without contacting a service center. Built-in lithium battery is used as a power supply. It could be charged from any charger for smart phone with the power 5V via USB-C.

All measurements are taken with 2 buttons only. First button is measurement. Second button is used for switching off. The 3-line, high-contrast, permanently backlit display makes it easy to work at any time of the day in any light.

|                       |                      |
|-----------------------|----------------------|
| Range, m              | 25                   |
| Accuracy, mm          | $\pm 3$              |
| Dust/water protection | IP 54                |
| Power supply          | 3,7V /Li-ion battery |

### COMPLETE SET:

device, cable for charger, plastic box, operating manual

## COSMO MICRO 25



ART. A00670

## Laser distance meter

Laser distance meter ADA COSMO Mini is a compact and comfortable model of laser range finder. It is a junior model in the special COSMO product range. It has minimum quantity of functions for measurements and calculations. Due to its ergonomic and compact design with rubber protective coating, ADA COSMO Mini fits perfectly in a hand. ADA COSMO Mini is ideal choice for indoor operations. It will be irreplaceable instrument for finisher, joiner, window setter, designer. Compact and light laser distance meter for construction site and home.

Laser distance meter ADA COSMO Mini 40 is a new and compact instrument for measurements up to 40 m. It is a most suitable laser distance meter in the special COSMO product range. It has minimum quantity of functions for measurements and calculations. Due to its ergonomic and compact design with rubber protective coating, ADA COSMO Mini 40 fits perfectly in a hand. It is a light instrument. It weighs just 120 g. High protection from shocks during falling. Water and dust protection – IP 54.

Laser distance meter ADA COSMO Mini 40 is ideal choice both for indoor and outdoor operations. Appropriate Instrument for construction and home.

### COMPLETE SET:

device, batteries, plastic box, operating manual

|                       |            |            |
|-----------------------|------------|------------|
| Range, m              | 0.05 to 30 | 0.05 to 40 |
| Accuracy, mm          | $\pm 3$    | $\pm 2$    |
| Dust/water protection | IP 54      | IP 54      |
| Power supply          | 2xAAA /1.5 | 2xAAA /1.5 |

## COSMO MINI / COSMO MINI 40



**COSMO MINI**  
ART. A00410



**COSMO MINI 40**  
ART. A00490



# COSMO 50 / 70 / 100

Laser distance meter



Laser distance meter ADA COSMO 50/70/100 are professional laser distance meters that is very simple and easy in usage.

Ergonomic design of the housing for convenient measurements. Protective ribbed parts are at the top and bottom parts of the instrument.

They protect the housing from damages.

**COMPLETE SET:**

device, batteries, plastic box, operating manual



**COSMO 50**  
ART. A00491



**COSMO 70**  
ART. A00429



**COSMO 100**  
ART. A00412

|                       |              |              |              |
|-----------------------|--------------|--------------|--------------|
| Range, m              | 0.05 to 50   | 0.05 to 70   | 0.05 to 100  |
| Accuracy, mm          | ±1.5         | ±1.5         | ±1.5         |
| Power supply          | IP 54        | IP 54        | IP 54        |
| Dust/water protection | 2xAAA /1.5 V | 2xAAA /1.5 V | 2xAAA /1.5 V |



## Laser distance meter

Laser distance meter with slope function ADA COSMO 60 GREEN is a new laser distance meter with green laser. Protective ribbed parts protect the housing from damages. Laser distance meter fits perfectly in the hand. Water-proof and dust-proof membrane keys.

|                       |             |
|-----------------------|-------------|
| Range, m              | 0.05 to 60  |
| Accuracy, mm          | ±1,5        |
| Power supply          | 2xAA /1.5 V |
| Dust/water protection | IP 54       |

**COMPLETE SET:** device, batteries, operating manual

## COSMO 60 GREEN



ART. A00629

## Laser distance meter

Laser distance meter ADA COSMO 120 Video is a novelty of 2017 on the market of professional laser distance meters. Unique combination of digital viewer and 360° tilt sensor allow to take measurements that are impossible to take with ordinary laser distance meters.

Built-in digital viewer ADA COSMO 120 Video allows to take measurements with high accuracy in unfavorable light conditions. This is a decided advantage when work outside in sunny weather. Even if the red dot of laser pointer is invisible, it is possible to aim laser distance meter at the object with the help of reticule on the display.

|                       |                           |
|-----------------------|---------------------------|
| Range, m              | 0.05 to 120               |
| Accuracy, mm          | ±1,5                      |
| Power supply          | 3xAAA /1.5 V/Li-ion 3,7 V |
| Dust/water protection | IP 54                     |

**COMPLETE SET:** device, batteries, operating manual

## COSMO 120 VIDEO



ART. A00502

## Laser distance meter

Laser distance meter ADA COSMO 150 Video is a novelty of 2016 on the market of professional laser distance meters. Unique combination of digital viewer and 360° tilt sensor allow to take measurements that are impossible to take with ordinary laser distance meters.

Easy and accurate aiming – viewer with 3X zoom. Built-in digital viewer ADA COSMO 150 Video allows to take measurements with high accuracy in unfavorable light conditions. This is a decided advantage when work outside in sunny weather. Even if the red dot of laser pointer is invisible, it is possible to aim laser distance meter at the object with the help of reticule on the display.

|                       |             |
|-----------------------|-------------|
| Range, m              | 0.05 to 150 |
| Accuracy, mm          | ±1,5        |
| Power supply          | 2xAA /1.5 V |
| Dust/water protection | IP 54       |

**COMPLETE SET:** device, batteries, operating manual

## COSMO 150 VIDEO



ART. A00475




# DIGITEO 5/20



## Electronic theodolite

Electronic theodolites ADA DigiTeo 5/20 are theodolites with electronic readings of indications that are shown on the LCD display with 5" и 20" angular accuracy, respectively. They are additionally equipped with the electronic compensator that informs about out of leveling range and make the corrections to the values.

|                                  | <b>DIGITEO 20</b><br>ART. A00229 | <b>DIGITEO 5</b><br>ART. A00227 |
|----------------------------------|----------------------------------|---------------------------------|
| Accuracy (standard deviation), " | 20                               | 5                               |
| Magnification, x                 | 30                               | 30                              |
| Data transfer to PC              | RS232                            | RS232                           |
| Battery                          | 1 accum. / 4xAA                  | 1 accum. / 4xAA                 |



### COMPLETE SET:

device, case, accumulator, charger, plummet, adjustment pin, screwdriver, brush, cleaning flannel-cloth, desiccant, operating manual

# BASIS



ART. A00117

## Auto level

Auto level ADA BASIS is designed for the stable and accurate operation on the construction site. It is equipped with automatic air compensator. When the instrument is adjusted with circular level, the mechanism of automatic compensator fixes the line of sight into the horizon.

|   |     |
|---|-----|
| Accuracy (1 km double run leveling), mm | 2,5 |
| Magnification, x                        | 20  |
| Objective aperture, mm                  | 38  |
| Minimum focus, m                        | 0,3 |

### COMPLETE SET:

device, case, key for adjustment stadia hairs, hex-nut wrench, stadia plumb, operating manual

# RUBER-X32



ART. A00121

## Auto level

Auto level ADA RUBER-X32 is designed for every day usage under different weather conditions. The device is equipped with magnetic compensator. Rubberized housing will reduce the possibility of the level slipping out of your hands. Auto level is equipped with securely fixed mirror for checking bubble level and open-type limb for angular measurements.

|   |     |
|---|-----|
| Accuracy (1 km double run leveling), mm | 1,5 |
| Magnification, x                        | 32  |
| Objective aperture, mm                  | 36  |
| Minimum focus, m                        | 1,0 |

### COMPLETE SET:

device, case, instrument for adjustment stadia hairs, hex-nut wrench, stadia plumb, operating manual



## Auto level

Auto level ADA PROF - X32 is equipped with fast-acting automatic compensator with magnetic damper and high quality coated optics, which significantly distinguishes them from other models of levels. When the instrument is adjusted with circular level, the mechanism of automatic compensator fixes the line of sight into the horizon.

|   |     |
|---|-----|
| Accuracy (1 km double run leveling), mm | 1,5 |
| Magnification, x                        | 32  |
| Objective aperture, mm                  | 42  |
| Minimum focus, m                        | 0,3 |

### COMPLETE SET:

device, case, instrument for adjustment stadia hairs, hex-nut wrench, stadia plumb, operating manual

## PROF - X32



ART. A00119

## Pyrometer

Infrared Thermometer ADA TEMPRO 300/550 is a compact infrared pyrometer of a gun-type. It provides highest possible comfort during application. Simple measuring is done by one «trigger» push.

### TEMPRO 300

ART. A00222

|                         |   |   |
|-------------------------|---|---|
| Measuring range, °C     | -32...+350  | -50...+550  |
| Optical resolution, D:S | 12:1  | 12:1  |
| Accuracy                | ±3°C at t≤0°C / ±2°C at 0°C<t≤100°C / ±1°C at t>100°C | ±3°C at t≤0°C / ±2°C at 0°C<t≤100°C / ±1°C at t>550°C |
| Thermal emissivity      | 0,95  | 0,95  |
| Spectral range, mcm     | 8...14  | 8...14  |

### TEMPRO 550

ART. A00223

### COMPLETE SET:

pyrometer, battery 9V, operating manual

## TEMPRO 300 / 550



## Pyrometer

Infrared Thermometers ADA TEMPRO 700/900 – are of high quality temperature infrared pyrometers. They are used for industrial temperature measurements.

### TEMPRO 700

ART. A00224

|                         |            |            |
|-------------------------|------------|------------|
| Measuring range, °C     | -50...+700 | -50...+950 |
| Optical resolution, D:S | 12:1       | 12:1       |
| Accuracy                | ±1,5       | ±1,5       |
| Thermal emissivity      | 0,1...1    | 0,1...1    |
| Spectral range, mcm     | 8...14     | 8...14     |

### TEMPRO 900

ART. A00225

### COMPLETE SET:

pyrometer, battery 9V, operating manual

## TEMPRO 700 / 900





# TEMPRO 650 HYGRO



ART. A00658

## Pyrometer

The ADA TemPro 650 Hygro provides non-contact temperature measurements from  $-50^{\circ}\text{C}$  to  $+650^{\circ}\text{C}$  with sensibility of  $\pm 1.5^{\circ}\text{C}$ . The ADA TemPro 650 Hygro pyrometer has 12:1 optical resolution for remote measurements. TemPro 650 Hygro combines the ability to measure both temperature and humidity of the ambient air. It is used by professionals involved in the maintenance of heating systems, ventilation, air conditioning, industrial and electrical equipment.

The main difference in the pyrometer ADA TemPro 650 Hygro is the measurement of humidity and ambient air temperature, thermocouple type-k, manually change the coefficient of thermal radiation.

The ADA TemPro 650 Hygro is a compact infrared pistol type pyrometer that is as easy to use as possible. Laser target marker makes it possible to perform fast, accurate measurements, «to take unerring aim».

|   |  |
|---|--|
| Measuring range, °C                       | -50...+650 / -40...+500 (thermocouple type-K)  |
| Ambient temperature measurement range, °C | -20...+60  |
| Emissivity                                | range 0.10-1.00 (by default 0.95)  |
| Optical resolution, (D:S)                 | 12:1   |
| Accuracy                                  | $-50^{\circ}\text{C} \sim 0^{\circ}\text{C}: \pm 3^{\circ}\text{C}; 0^{\circ}\text{C} \sim 650^{\circ}\text{C}: \pm 1.5\% \pm 1.5^{\circ}\text{C}$ |
| Power supply                              | 2x1.5V (AAA)   |
| Dew point temperature measurement, °C     | -10...+50  |
| Relative humidity measurement accuracy, % | $\pm 5$  |
| Weight, dimensions                        | 202 g, 177mm×108mm×49mm  |

### COMPLETE SET:

device, batteries, operating manual

# BODYTEST



ART. A00659

## Infrared thermometer

The ADA BODYTEST pyrometer is a replacement for a mercury or electronic thermometer. Fast and highly accurate temperature measurement in just 1 second (not a medical product).

The ADA BODYTEST pyrometer offers two modes: temperature measurement on persons or temperature measurement on surfaces. One button to toggle between modes.

When the ADA BODYTEST measures the human body temperature the LCD display shows a green light at temperatures below  $37.3^{\circ}\text{C}$ , an orange light at  $37.4^{\circ}\text{C}$  and a red light at temperatures above  $38^{\circ}\text{C}$ . Additionally, an audible alarm sounds. The alarm temperature limits can be adjusted silent mode. The alarm temperature limits can be adjusted.

The ADA BODYTEST pyrometer has a silent mode so that you can comfortably measure your baby's temperature while he sleeps. This makes it easy to check the temperature of small children.

If the ADA BODYTEST Pyrometer shows an abnormal temperature reading, it can easily be calibrated..

|   |  |
|---|--|
| Measuring range, °C                                 | +32...+43 (human body) / 0...+100  |
| Measurement distance, cm                            | 1-3  |
| Accuracy, °C  | $\pm 0.3$ (human body) / $\pm 2$   |
| Temperature resolution, °C                          | 0.1  |
| Illumination while measuring body temperature       | Green: at a temperature of $\leq 37.3^{\circ}\text{C}$<br>Orange: at a temperature of $37.4^{\circ}\text{C}$<br>Red: at a temperature of $\geq 38^{\circ}\text{C}$ |
| Operating conditions: temperature, °C / humidity, % | 16-35°C / $\leq 85\%$  |
| Power supply  | 2x1.5V (AAA)   |

### COMPLETE SET:

device, batteries, operating manual



## Thermal imaging camera

ADA TEMPRO VISION 120 – is an entry-level thermal imager camera. This model is designed specifically for builders, electricians, engineers of heating, ventilation and air conditioning systems, mechanics, production technologists. The device allows you to capture infrared (IR) images along with measured / additional data and save them on a memory card for subsequent analysis of the received data, as well as reporting.

|                           |   |
|---------------------------|---|
| Measuring range, °C       | -20°C-150°C, 100°C-400°C (Automatic switch off)   |
| Optical resolution, (D:S) | 130:1   |
| Accuracy, °C              | ±2°C or ±2%, depending on what is higher (measured temperature ≥0°C, ambient air temperature 15°C ~ 30°C) |
| IR resolution             | 120×90  |
| Spectral response, um     | 7.5~14  |
| Thermal sensitivity       | 60 mk   |
| Power supply              | Li-ion battery  |
| Dimensions                | 194×61.5×76 mm  |

### COMPLETE SET:

device, charger, case, operating manual

## TEMPRO VISION 120



ART. A00685

## Thermal imaging camera

ADA TEMPRO VISION 256 PROFESSIONAL – is a professional thermal imager camera. The model provides excellent thermal image quality. The device allows you to capture infrared (IR) images along with measured / additional data and save them on a memory card. The resolution of the IR image is 256x192 pixels. Automatic hot/cold spot recognition. Setting the ambient temperature in the menu helps to obtain the most accurate temperature measurements of objects.

|                           |   |
|---------------------------|---|
| Measuring range, °C       | -20°C-150°C, 100°C-550°C (Automatic switch off)   |
| Optical resolution, (D:S) | 266:1   |
| Accuracy, °C              | ±2°C or ±2%, depending on what is higher (measured temperature ≥0°C, ambient air temperature 15°C ~ 30°C) |
| IR resolution             | 256×192   |
| Spectral response, um     | 7.5~14  |
| Thermal sensitivity       | 45 mk   |
| Power supply              | Li-ion battery  |
| Dimensions                | 194×61.5×76 mm  |

### COMPLETE SET:

device, charger, case, operating manual

## TEMPRO VISION 256 PROFESSIONAL



ART. A00686



# TEMPRO VISION



ART. A00519

## Thermal imager

Thermal imager ADA TemPro VISION is an electronic device for temperature measurement in IR spectrum. Temperature measuring range is  $-20^{\circ}\text{C}$ ... $+350^{\circ}\text{C}$ . The device allows to fix visible and IR image together with measured data and save them on SD-card for the next analysis and report preparation. High resolution IR image is achieved by the data processing from the detector (60x60 pixels). It allows to increase the image quality twice.

Thermal imager ADA TemPro VISION is ideal for thermal imaging survey both at home and on the production: monitoring and detection of hidden heating systems and their breakage, searching of heat leakage and critical temperatures, safety monitoring of the temperature of working or voltage-carrying equipment, report preparation.

|                          |   |
|--------------------------|---|
| IR temperature range, °C | -20...+350  |
| Accuracy                 | $\pm 2\%$ / $\pm 2^{\circ}\text{C}$ / $\pm 3,6^{\circ}\text{F}$ |
| Focus mode               | fixed   |
| Image storage            | Micro SD  |
| Display                  | color LCD display 2,5"  |
| Power supply             | 4x AA ,1,5V   |

**COMPLETE SET:**  
device, battery, SD-card, case, operating manual

# ZHT 70 (2 IN 1)



ART. A00518

## Moisture meter of wood and building materials/ambient temperature meter

ADA ZHT 70 (2 in 1) is a moisture meter that measures the moisture by detecting the resistivity with the help of 2 electrodes. Electronic scheme processes received signal and moisture content is shown on the LCD display. This device is designed for moisture measurement of the wood, plaster and concrete. Moisture meter is used in the construction, in warehouses of sawn timber, wood drying plants.



|                                 |  |
|---------------------------------|--|
| Moisture range:                 | 1-70%RH  |
| Wood (3 types)                  | $\pm 2\%$ / $\pm 2^{\circ}\text{C}$ / $\pm 3,6^{\circ}\text{F}$  |
| Construction materials (1 type) | 0.1 ~ 2.4% RH  |
| Temperature range               | $-20$ ~ $+70^{\circ}\text{C}$ / $-4$ ~ $158^{\circ}\text{F}$ ; $\pm 1.5^{\circ}\text{C}$ / $2.7^{\circ}\text{F}$ |
| Power supply                    | 1x9B "6F22"  |

**COMPLETE SET:**  
detector, battery, operating manual



## Electronic thermometer

Electronic thermometer ADA THERMOTESTER 330 – is a compact device for contact temperature measurement. Field of application is varied.

Temperature measurement of food stuffs during storage and cooking. Temperature control of liquids: water, oil. Temperature measurement of soil, asphalt mix and so on.

|  |                |
|--|----------------|
| Temperature range, °C                  | -50 to +330    |
| Operating temperature: temperature, °C | -20...+50      |
| Resolution, °C                         | 0.1            |
| Detection of Min/Max temperature       | v              |
| Power supply                           | 1x3V "CR 1225" |

### COMPLETE SET:

electronic thermometer, battery, operating manual

## THERMOTESTER 330



ART. A00513

## Anemometer

Both anemometers ADA AEROTEMP 30 are used for air velocity measurement and its temperature. The device is ideal for the application on the environmental monitoring stations, for checking ventilation, air conditioning, in sailing, aviation and parachute sport.

|                                       |  |
|---------------------------------------|--|
| Air velocity range                    | 0.4...30 m/s                               |
| Temperature range, °C                 | -20...+70                                  |
| Power supply                          | 3 x AAA/1,5V                               |
| Sensors                               | Plastic van sensor, temperature sensor NTC |
| Measured parameters                   | m/s, f/min, sea mile/h, km/h, m/h, °C, °F  |
| Dust/water protection                 | -  |
| Operating conditions: temperature, °C | -20...+60                                  |

### COMPLETE SET:

device, batteries, operating manual

## AEROTEMP 30



ART. A00515

## Anemometer

Both anemometers ADA IP 65 are used for air velocity measurement and its temperature. The device is ideal for the application on the environmental monitoring stations, for checking ventilation, air conditioning, in sailing, aviation and parachute sport.

|                                       |  |
|---------------------------------------|--|
| Air velocity range                    | 0...30 m/s                                 |
| Temperature range, °C                 | -10...+45                                  |
| Power supply                          | CR2032 3.0V                                |
| Sensors                               | Plastic van sensor, temperature sensor NTC |
| Measured parameters                   | m/s, f/min, sea mile/h, km/h, m/h, °C, °F  |
| Dust/water protection                 | IP65                                       |
| Operating conditions: temperature, °C | -10...+45                                  |

### COMPLETE SET:

anemometer, battery, operating manual

## AEROTEMP IP 65



ART. A00546



# WALL SCANNER 50



ART. A00506

## Wire and metal detector

Wire and metal detector ADA WALL SCANNER 50 is used for the detection of hidden wiring in the walls, floors or connection boxes and metal: plasterboard profile, reinforcing steel. It is used in different spheres: construction, repair and so on.

|   |             |
|---|-------------|
| Depth of the magnetic metal detection, mm | 50          |
| Operating temperature, °C                 | -10...+50   |
| Live wire detection                       | 70...600 V  |
| Power supply                              | 1x9B "6F22" |

### COMPLETE SET:

detector, battery, operating manual

# WALL SCANNER T



ART. A00586

## Metal, wire and wood detector

ADA Wall Scanner T metal and wire detector is intended for detection of ferrous and non-ferrous metals, live wires and wood structures in walls, ceilings and floor. It's used in various fields of application: construction, repair, etc.

|   |             |
|---|-------------|
| Depth of the magnetic metal detection, mm | 50          |
| Batteries/power, Pcs. x Type/V            | 4xAAA 1,5 V |
| Depth of the live wire detection, mm      | 50          |
| Depth of wood detection, mm               | 20          |
| Adjustment                                | automatic   |

### COMPLETE SET:

detector, soft bag, battery, operating manual

# WALL SCANNER 120 PROF / 80



## Metal, wire and wood detector

ADA WALLSCANNER 80 / ADA WALLSCANNER 120 PROF - is a wire and wood detector is intended for detection of ferrous and non-ferrous metals, live wires and wood structures in walls through electric signal. Digital display with backlight - measurement values are easy to read. Scanning function of the electric wiring allows to define its location and doesn't allow to react on other objects (e.g. reinforcing steel).

|   | WALLSCANNER 120 PROF<br>ART. A00485 | WALLSCANNER 80<br>ART. A00466 |
|---|-------------------------------------|-------------------------------|
| Depth of the magnetic metal detection, mm     | 120                                 | 80                            |
| Depth of the non-magnetic metal detection, mm | 80                                  | 60                            |
| Depth of the live wire detection, mm          | 50                                  | 50                            |
| Depth of wood detection, mm                   | 38                                  | 20                            |
| Power supply                                  | 1x9V "6F22"                         |                               |

COMPLETE SET: detector, bag, battery, operating manual



## Thermo-hygrometer

Humidity and measurement device ADA ZHT100-70 – is a digital tool for humidity and temperature measurement 2 in 1! Field of application: control of air in the room, ventilation system and so on.

|                       |                     |   |
|-----------------------|---------------------|---|
| Humidity              | Measuring range     | 0~100%  |
|                       | Measuring accuracy  | ±3% (20 to 80%); ±4.5% (0 to 20% and 80 to 100) |
| Temperature           | Measuring range     | -20°C~70°C / -4°F to 158°F                      |
|                       | Measuring accuracy  | ±1.0°C/±1.8°F                                   |
| Dew point temperature | Measuring range     | 20°C~70°C / -4°F до 158°F                       |
|                       | Measuring accuracy* | ±1.5°C/±2.7°F                                   |
| Power supply          |                     | 3x1.5V AAA                                      |

\*Accuracy depends on environmental conditions - 25°C; 40 RH%100 RH%

### COMPLETE SET:

detector, battery, operating manual

## ZHT 100-70



ART. A00516

## Sound level meter

Sound level meter ADA ZSM135 is widely used in acoustical measurements, automobile industry, in environmental protection, health services and so on.

|  |                      |
|--|----------------------|
| Level/accuracy of measuring range      | 35dB~135dB/±2.0dB    |
| Frequency range                        | 31.5Hz ~ 8KHz        |
| Frequency weighting                    | A                    |
| Range/accuracy of measured temperature | -20°C ~ +70°C/±1.5°C |
| Power supply                           | 3 x AAA, 1,5V        |

### COMPLETE SET:

detector, battery, operating manual

## ZSM 135



ART. A00517

## Noncontact voltage detector AC

ZAC1000 PLUS is designed for noncontact detection of voltage in the sockets, switches, wires and cables and also for detection of the breakage place of the wire. Detector is equipped with the flashlight for operation in unlit places.

|              |                         |
|--------------|-------------------------|
| Detection    | AC voltage, 90...1000 V |
| Power supply | 2xAAA/1,5V              |
| Power supply | 2xAAA/1,5V              |

### COMPLETE SET:

detector, battery, operating manual

## ZAC 1000 PLUS



ART. A00689



# ANGLERULER 20/30/50



## Electronic angle meter

Electronic angle meters ADA ANGLE RULER 20/30/50 are designed for angle measurement. These devices have built-in electronic angle sensor. Data are displayed on the built-in LCD digital display. Set zero value for measuring relative angles at any position of the instrument. AngleRuler is ideal for fitter's, construction, carpenter's and finishing works.

|                 | <b>ANGLERULER 20</b><br>ART. A00394 | <b>ANGLERULER 30</b><br>ART. A00395 | <b>ANGLERULER 50</b><br>ART. A00396 |
|-----------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Length, cm      | 20                                  | 40                                  | 50                                  |
| Measuring range | 0...360                             | 0... 360                            | 0...360                             |
| Accuracy        | ±0,3                                | ±0,3                                | ±0,3                                |
| Power supply    | 1xCR2032, 3V                        | 1xCR2032, 3V                        | 1xCR2032, 3V                        |

### COMPLETE SET:

electronic angle meter, battery, operating manual

# SH 225



ART. A00191

## Test hammer (sclerometer)

Sclerometer SH 225 is designed to determine the strength of concrete in concrete and reinforced concrete structures and products by the method of elastic rebound. The SH 225 sclerometer is a versatile, simple, reliable device and can be used indoors and outdoors.

|   |                 |
|---|-----------------|
| Value of the scale division, relative units                                   | 2               |
| The hardness of the working surfaces of the striker and the rebound pole, HRC | no less than 60 |
| Sphere radius of the rebound pole, mm   | 25±1            |
| Product dimensions (length / Ø max), mm                                       | 280/43          |

### COMPLETE SET:

device, batteries, operating manual

# MECHANIC 150/150 PRO



## Digital caliper

Digital calipers ADA MECHNIC 150/150 Pro are used for taking external and internal measurements of different objects. is fully made of stainless steel. Results of the measurement are displayed on the LCD display. Accurate and quality manual measurement instrument.

|                | <b>MECHANIC 150</b><br>ART. A00379 | <b>MECHANIC 150 PRO</b><br>ART. A00380 |
|----------------|------------------------------------|--|
| Length, mm     | 0-150                              | 0-150                                  |
| Resolution, mm | 0.01                               | 0.01                                   |
| Accuracy, mm   | ±0.03                              | ±0.03                                  |
| Power supply   | 1xSR44/1,5V                        | 1xSR44/1,5V                            |

### COMPLETE SET:

digital caliper, battery, operating manual



## Coating thickness tester

ADA PAINTMETER 1500 / PAINTMETER 1800 is a professional coating thickness tester. It is designed to measure coatings on ferrous and non-ferrous metals up to 1,5 mm. It is used for the operation in laboratories, workshops, in the chemical, automotive, shipbuilding and aviation industries.

|                        | <b>PAINTMETER 1500</b><br>ART. A00581   | <b>PAINTMETER 1800</b><br>ART. A00656   |
|------------------------|---|---|
| Measuring range, $\mu$ | 0 ~ 1500  | 0 ~ 1800  |
| Resolution             | 0.1 $\mu$ m (<100 $\mu$ m),<br>1 $\mu$ m ( $\geq$ 100 $\mu$ m) 0~1500 $\mu$ m | 0.1 $\mu$ m (<100 $\mu$ m),<br>1 $\mu$ m ( $\geq$ 100 $\mu$ m) / 0,1 mil / 0,001 mm                                 |
| Accuracy               | $\pm$ 5 $\mu$ m ( $\leq$ 150 $\mu$ m) $\pm$ 3%H+1 $\mu$ m<br>(>150 $\mu$ m)   | $\leq$ 150 $\mu$ m( $\mu$ m), $\pm$ 5 $\mu$ m( $\mu$ m)<br>>150 $\mu$ m( $\mu$ m), $\pm$ ( 3%H+1 $\mu$ m( $\mu$ m)) |
| Power                  | 3.7V (lithium battery 1000 mAh)   | 2x1,5V, AAA   |
| Complete set           | device, batteries,<br>operating manual  | device, bag, batteries, calibrating<br>plates, operating manual   |

## PAINTMETER 1500 / 1800



ART. A00581

ART. A00656


## Electronic angle meter

Electronic angle meter ADA ANGLEMETER 30/40 is designed for angle measurement. It is made of anodized aluminium. Ideal for carpentry and joinery.

|                 | <b>ANGLEMETER 30</b><br>ART. A00494 | <b>ANGLEMETER 40</b><br>ART. A00495 |
|-----------------|-------------------------------------|-------------------------------------|
| Length, cm      | 30                                  | 40                                  |
| Measuring range | 0...225                             | 0...225                             |
| Accuracy        | $\pm$ 0,3                           | $\pm$ 0,3                           |
| Power supply    | 1xCR2032, 3V                        | 1xCR2032, 3V                        |

**COMPLETE SET:** electronic angle meter, battery, operating manual

## ANGLEMETER 30/40



## Electronic angle meter

Electronic angle meter ADA ANGLEMETER 45 is an accurate angle meter that is made of anodized aluminium. Convenient readable LCD display, ergonomic design. Convenient and easy to use. Ideal for carpentry and joinery. Use the modes of calculation of cut angles when working with trimming saw, e.g. when setting floor molding in the angles of the room.

|                 |             |
|-----------------|-------------|
| Length, cm      | 45          |
| Measuring range | 0...225     |
| Accuracy        | $\pm$ 0,1   |
| Power supply    | 2xAAA, 1,5V |

**COMPLETE SET:** electronic angle meter, battery, operating manual

## ANGLEMETER 45



ART. A00408



# PRODIGIT MICRO



ART. A00335

## Digital angle meter

Digital angle meter ADA PRO DIGIT MICRO is designed for fast and accurate determination of the angular deflection from the horizontal or vertical surface. The housing of instrument is made of lightweight and durable aluminum alloy.

|                      |            |
|----------------------|------------|
| Working range        | 4/90       |
| Measurement accuracy | ±0,2       |
| Resolution           | 0,05       |
| Power supply         | 2xAAA/1,5V |

### COMPLETE SET:

digital angle meter, battery, screwdriver, operating manual

# PRODIGIT MINI



ART. A00378

## Digital level

Digital angle meter ADA PODIGIT MINI is a light and accurate level for the determination of the surface slope. Housing of the tool is made of light and strong plastic.

|                      |                  |
|----------------------|------------------|
| Working range        | 4*90/1000/100/12 |
| Measurement accuracy | ±0,15            |
| Resolution           | 0,05             |
| Power supply         | 2xAAA/1,5V       |

### COMPLETE SET:

digital angle meter, battery, operating manual

# PRODIGIT MARKER



ART. A00671

## Digital angle meter(with laser marker)

Digital angle meter ADA ProDigit MARKER is designed for fast and accurate determination of the angular inclination from the horizontal or vertical surface. Two built-in laser beams prolongate a line of the level. Attach the level to the wall and turn it to the desired angle, focusing on the display readings. The laser line will show the slope at a distance from the tool.

The working surface is equipped with magnets. Special mode for measuring relative angles. The display has a backlight for operation in dark places. The housing of the tool is made of light and strong plastic with aluminum frame. The built-in lithium battery is used as a power source.

|                      |              |
|----------------------|--------------|
| Working range, °     | 4*90         |
| Inclination accuracy | ±0,2         |
| Resolution           | 0,05         |
| Power supply         | 3.7V battery |

### COMPLETE SET:

digital angle meters, bag, cable USB - Type-C, operating manual



## Digital angle meter

|                      |            |
|----------------------|------------|
| Working range        | 4°90       |
| Measurement accuracy | ±0,2       |
| Resolution           | 0,05       |
| Power supply         | 2xAAA/1,5V |

### COMPLETE SET:

digital angle meter, battery, operating manual

ART. A00481

# PRODIGIT RUMB



Digital angle meter ADA PRODIGIT RUMB is a light and accurate level for the determination of the surface slope.

Housing of the tool is made of light and strong plastic. Working surface is equipped with magnets. They allow to set it on the steel structures.





# PROLEVEL 40/60



## Digital level

Digital levels ADA PROLEVEL 40/60 are designed for tilt measurement of parts and surfaces. Convenient readable digital LCD display shows deviation from horizontal/vertical.

Data are received from the slope sensor. Automatic calibration for accurate operation. Built-in bubble levels allow to run double check together with electronic slope sensor or to work with regular level.

Built-in magnets on the bottom allow to set the instrument on the steel structure. Ideal choice for different kind of operation both inside and outside.

|                         | <b>PROLEVEL 40</b><br>ART. A00381 | <b>PROLEVEL 60</b><br>ART. A00391 |
|-------------------------|-----------------------------------|-----------------------------------|
| Length, cm              | 40                                | 60                                |
| Angle measurement range | 4x90                              | 4x90                              |
| Resolution/accuracy     | 0.1/0.2                           | 0.1/0.2                           |
| Power supply            | 2xAAA, 1,5V                       | 2xAAA, 1,5V                       |

### COMPLETE SET:

digital level, batteries, operating manual

# TITAN 40 PLUS/ 60 PLUS/ 80 PLUS/ 100 PLUS



## Spirit levels

Spirit levels ADA TITAN 40 PLUS/60 PLUS/80 PLUS/100 PLUS are made of hard strong aluminum shape with two milled working surfaces. Such surface provides additional measurement accuracy.

Use reflective surface that is located near the bubble level to work in a room with poor lighting.

Magnets on the bottom are used for the attachment to the metallic surfaces. Three bubble levels allow to control horizontal and vertical deviations. Plastic rubber caps on the ends are used for fall protection and prevention from slip during measurements on the inclined planes.

|                          | <b>TITAN 40 PLUS</b><br>ART. A00509 | <b>TITAN 60 PLUS</b><br>ART. A00510 |
|--------------------------|-------------------------------------|-------------------------------------|
| Length, cm               | 40                                  | 60                                  |
| Bubble level accuracy, ° | ±0.029                              | ±0.029                              |

|                          | <b>TITAN 80 PLUS</b><br>ART. A00511 | <b>TITAN 100 PLUS</b><br>ART. A00512 |
|--------------------------|-------------------------------------|--------------------------------------|
| Length, cm               | 80                                  | 100                                  |
| Bubble level accuracy, ° | ±0.029                              | ±0.029                               |



## Measuring wheels

Electronic road measuring wheel ADA Wheel 50 Digital is the instrument for distance measurement. Road wheels are used in road building, in STSI, for planning and mapping, when measuring the distance of outside communication lines, for cadastral surveys.

ADA Wheel 1000 Digital is a digital measuring instrument that is used for fast and accurate distance measurements in all weather conditions. Replacing the measuring tape and mechanical measuring wheel it measures distances and displays the results in digital format. A turn of the wheel is 1000 cm. The quantity of turns is calculated with the help of electronic sensor. No gear-wheels and wearing pieces.

Measuring wheel ADA Wheel 100 is used for road marking even if the surface is rough. Measuring wheel allows to calculate square, length of the buildings and fences. It has foldable handle.

|                          | <b>WHEEL 100</b><br>ART. A00113 | <b>WHEEL 50 DIGITAL</b><br>ART. A00416 | <b>WHEEL 1000 DIGITAL</b><br>ART. A00417 |
|--------------------------|---------------------------------|--|--|
| Maximum distance, m      | 10 000                          | 10 000                                 | 10 000                                   |
| Minimum counter step, cm | 10                              | 10                                     | 10                                       |
| Circumference, cm        | 100                             | 50                                     | 100                                      |

### COMPLETE SET:

measuring wheel, soft bag, operating manual, battery 2x1.5 V / AAA (only for Digital)

## WHEEL 100/ 50 DIGITAL/ 1000 DIGITAL



WHEEL 100  
ART. A00113



WHEEL 50 DIGITAL  
ART. A00416

WHEEL 1000 DIGITAL  
ART. A00417

## Measuring tapes with steel blade

ADARUBTAPE 3, 5, 8, 10 – is a reliable and easy to use measuring tape which is protected by ribbed rubber element, shockproof. Clear and easy to read graduation and classical system of constant fixation with the blade lock at the front side. The width of the blade RubTape is from 16 mm to 32 mm. ADA RubTape 3, 5, 8, 10 is ideal choice for every day usage!

|                 | <b>RUBTAPE 3</b><br>ART. A00155 | <b>RUBTAPE 5</b><br>ART. A00156 | <b>RUBTAPE 8</b><br>ART. A00157 | <b>RUBTAPE 10</b><br>ART. A00154 |
|-----------------|---------------------------------|---------------------------------|---------------------------------|----------------------------------|
| Blade length, m | 3                               | 5                               | 8                               | 10                               |
| Blade width, mm | 16                              | 25                              | 25                              | 32                               |
| Blade           | steel                           | steel                           | steel                           | steel                            |

## RUBTAPE 3 / 5 / 8 / 10





# BASE

Universal mount



ADA BASE (MAGNETIC LIFT + WALL BRACKET) is an universal mount with micro lift for laser level mounting on any surfaces and height. It is designed for laser level mounting on any surfaces and height. It is made of high-strength plastic. Clamp and mount can be used separately.

It consists of two parts:

- ADA MAGNETIC LIFT (magnetic mount with micro lift for laser levels up to 1 kg)
- ADA WALL BRACKET (quick-release clamp with capture size up to 55 mm. It is used for laser levels mounting up to 2 kg on MAGNETIC LIFT).



ART. A00555

|                               |             |
|-------------------------------|-------------|
| Thread for laser level, inch  | 1/4; 5/8    |
| Adjustment range, mm          | 0 - 110     |
| Capture size of the clamp, mm | 0.5 - 55    |
| Dimensions, mm                | 226x160x107 |



## Magnetic mount

ADA MAGNETIC LIFT is a magnetic mount with micro lift for line lasers (up to 1 kg). The mount is made of high-strength plastic resistant to impact. It's almost impossible to break or damage ADA MAGNETIC LIFT. It's specially designed for professional use in aggressive construction site conditions. Strong neodymium magnets are used for mounting. Special hole for mounting on the tubes. Rubber parts for Prevention from slipping on the surface. Two threads  $\frac{1}{4}$  and  $\frac{5}{8}$  for mounting on the tripod.

|                                 |             |
|---------------------------------|-------------|
| Thread for installation, inches | 1/4; 5/8    |
| Adjustment range, mm            | 0 - 110     |
| Dimensions, mm                  | 226x160x107 |

## Clamp for magnetic mount

ADA WALL BRACKET is a quick-release clamp for laser level mounting (up to 2 kg) on the surfaces with the width from 0.5 mm to 55 mm. It's used as an additional mount clamp for ADA MAGNETIC LIFT. It's designed for the mounting on surfaces including non magnetic (tube, profile, timber and so on). Fast mounting and quick release is realized by pushing a large spring-loaded key.

|                               |           |
|-------------------------------|-----------|
| Capture size of the clamp, mm | 0.5 - 55  |
| Dimensions, mm                | 180x76x70 |

## Magnetic mount

Magnetic mount with micro lift for line lasers (up to 1 kg). The mount is made of high-strength plastic resistant to impact. It has a rotating platform with bearings. With the micro-screw, you can steer the vertical beams easily and precisely in the desired direction. Rubber pads are Adjustment is made with the help of double-sided handles. A special self-tapping eyelet is located at the top of the unit, for mounting on vertical walls, posts, etc.

|                             |             |
|-----------------------------|-------------|
| Adjustment range, mm        | 0-110       |
| Magnetic mount              | v           |
| Thread for tripod, inch     | 1/4 and 5/8 |
| Thread for line laser, inch | 1/4         |
| Dimensions, mm              | 150x160x107 |

## Universal mount with micro lift

Mount for line lasers (up to 1 kg) is made of high-strength plastic. Mounting on the surface is done with a clamp. The clamp is equipped with a special gutter for installation on pipes. There is a special eye at the top for a self-tapping screw for mounting on vertical walls, poles, etc.

|                               |      |
|-------------------------------|------|
| Capture size of the clamp, mm | 0-60 |
| Thread for line laser, inch   | 1/4  |

## MAGNETIC LIFT



ART.  
A00553

## WALL BRACKET



ART. A00554

## MAGNETIC LIFT 360



ART.  
A00661

## LASER FIX



ART.  
A00687



## SLIDER




### Adapter for magnetic mount

Adapter for installation of magnetic mount ADA MAGNETIC LIFT on the tripod-pillar ADA SILVER PLUS and ADA SILVER PLUS with tripod .

|                  |       |
|------------------|-------|
| Capture diameter | 32 mm |
| Capture type     | clip  |

ART. A00577

## SCREW-ADAPTER




### Screw-adapter from 5/8" to 1/4"

Metallic screw adapter is designed to go from an inch thread 5/8 « to 1/4». Use this adapter to set the tools with the thread 1/4" on the tripods, rods with the screw thread 5/8».

ART. A00489

## LR-60 / LR-60 GREEN



### Receiver for line laser levels

LR-60/LR-60 GREEN is a laser receiver. It is used for detection laser beam of line lasers (in the receiver mode). LR-60/LR-60 GREEN extends working range if you work under bright illumination and poor visibility of laser beam. Ideal for any outdoor application.

|                | LR-60<br>ART. A00478 | LR-60 GREEN<br>ART. A00499 |
|----------------|----------------------|----------------------------|
| Accuracy, mm/m | ±0,1                 | ±0,1                       |
| Power supply   | 1x9B 6LR61           | 1x9B 6LR61                 |

#### COMPLETE SET:

Receiver, batteries, fastening, instruction

## LASERMARKER 70



### Laser receiver

LASERMARKER 70— is a universal laser receiver. It is used for detection red or green laser beams of line lasers (in the Receiver mode). All information is shown on the LCD display. Laser target is placed on the back side of the receiver. It can be fixed with the help of mount or magnets.

|                        |               |
|------------------------|---------------|
| Accuracy (fine/coarse) | ± 1 mm/± 3 mm |
| Power supply           | 2xAAA/ 1.5V   |

ART. A00589



## Universal clamp

Universal clamp ADA Universal Mount is designed for attachment of light laser levels (up to 1 kg) on the wall, tripod and metallic surfaces. Attachment is made of metal in the form of angle. On one of its side there is:

- thread for the tripod 5/8" with adapter for setting laser level, e.g. tripod-rod ADA Silver;
- magnets for attachment on metallic surfaces, e.g. guides for gypsum plasterboard;
- hole for the screw to attach on the vertical surfaces, e.g. on the wall;

On the further side there is a mounting screw with the thread 1/4" for setting laser level. Universal attachment ADA Universal Mount is used for small laser levels with the thread 1/4".

ART. A00339

## UNIVERSAL MOUNT



## Telescopic aluminum leveling staff

Leveling staff for line laser ADA Laser Staff is used with receiver. It is specifically designed for use with rotating and line laser levels.

Height - 250 cm

Leveling staff makes the work easier when you operate with the receiver and line laser. You can use it when you align floor.

Leveling staff has two sections - lower, where there are numbers, and upper with zero mark, negative red scale and positive scale with graduation in millimeters. Leveling staff is made of strong, durable aluminium.

### COMPLETE SET:

device, batteries, operating manual

ART. A00230

## LASER STAFF



## Steel clamp

Reliable steel clamp with rotary screw for attachment to the surface at any angle. Place of attachment: door, heating radiator, handle of a window, cabinet door, stair railing, surface of a table, steps of a ladder and so on.

Rubber attachments protects surface from scratches when attaching. It is designed for use of level in large areas. It is used for small laser levels with the thread 1/4" and weight no more than 0.5 kg.

ART. A00345

## UNIVERSAL CLAMP





# MAGNETIC TARGET



## Magnet target

Red target ADA is used for marking in construction works. It's used with line laser. Inbuilt magnet allows to set target to the mounted profile or metalwork. It's very convenient when you need to level metal sections, pipes.

ART. A00210

# VISOR



ADA VISOR RED  
ART. A00126

Complete set:  
glasses, soft case

## Laser glasses/protective

ADA VISOR RED – laser glasses with special light filters for operation with red emission spectrum of laser instrument. Series ADA VISOR consists of protective glasses (PROTECT), contrast (CONTRAST) and sunglasses (BLACK), ADA VISOR GREEN – laser glasses with special light filter for the operation with green light spectrum. Glasses are made of durable polycarbonate with higher scratch resistance. Glasses from such material are shockproof and safety. Curved frame and large lenses for panoramic eye protection. Flexible rubberized temples are not afraid of bends and firmly hold glasses in any position.



ADA VISOR GREEN  
ART. A00624



ADA VISOR PROTECT  
ART. A00503



ADA VISOR CONTRAST  
ART. A00504



ADA VISOR BLACK  
ART. A00505

# SCREW ADAPTER WITH THREAD FROM 1/4" TO 5/8"



## Screw adapter with thread from 1/4" to 5/8"

This screw adapter is intended for moving from thread of 1/4" to thread of 5/8". It can be used for installation of devices with thread of 5/8" onto supports and bars with attachment screw thread of 1/4".

ART. A00321




## Metallic screw extender

Metallic screw extender is designed for installation of laser levels on the tripods and rods with the screw 5/8". Use this screw extender when adjusting legs of the tools interfere with the installation of the device on a tripod.

ART. A00274

## SCREW EX- TENDER WITH THREAD 5/8"



## Adapter

Adapter ADA BALL ADAPTER 5/8" to 1/4" allows to fix line laser with thread 1/4" on the tripods and clamps with thread 5/8". E.g. ADA CUBE can be set on the tripod-pillar ADA Silver Light. With the help of special ball joint in the upper part of the adapter it's possible to flip laser level 360° and set at any slope.

ART. A00373

## BALL ADAPTER 5/8" TO 1/4"



## Adapter

This screw adapter is intended for moving from thread of 1/4" to thread of 5/8". It can be used for installation of devices with thread of 5/8" onto supports and bars with attachment screw thread of 1/4".

ART. A00486

## SCREW ADAPT- ER WITH THREAD FROM 1/4" TO 5/8"



# SILVER PLUS/ SILVER PLUS WITH TRIPOD



## Tripod-pillar

Tripod-pillar ADA Silver PLUS is an aluminium pillar which consist of several sections. They are used for operation with different height up to 3.6 m. There is no need to use a ceiling during the operation with ADA SILVER PLUS with tripod.

ADA SILVER PLUS/SILVER PLUS with tripod comes with MAGNETIC LIFT and SLIDER.

|            |             |
|------------|-------------|
| Height, cm | 360         |
| Thread     | 5/8" / 1/4" |

## Complete ser



### SILVER PLUS ART. A00557

Thrust pad, adapter SLIDER, magnetic mount ADA MAGNETIC LIFT, connecting poles, bag



### SILVER PLUS WITH TRIPOD ART. A00556

Tripod, thrust pad, adapter SLIDER, magnetic mount ADA MAGNETIC LIFT, connecting poles, bag

# DIGIT 65/130 /167



DIGIT 65 ART. A00501

## Photo/video tripod

Photo/video tripod ADA Digit 65/130/160 is made of strong aluminium form and metal. It is designed for mounting different kinds of tools with thread 1/4. Models 130 allow to take off the installed device together with the head of attachment.



DIGIT 167  
ART. A00646



DIGIT 130  
ART. A00170



DIGIT 65  
ART. A00501

|                   |      |      |      |
|-------------------|------|------|------|
| Height max., cm   | 167  | 130  | 65   |
| Diameter head, mm | 65   | 55   | 50   |
| Thripod thread    | 1/4" | 1/4" | 1/4" |



## Elevating tripod

ADA Elevation 16B is a universal elevating tripod for mounting line lasers and cross liners. With clips.

ADA Elevation 63 is a heavy elevating tripod for mounting line lasers and cross liners. It is designed for mounting instruments with weight up to 10 kg. With clips.

ADA LIFT 34 with additional sections for installation of laser levels with max. working height 3,4 m.



**ELEVATION 16B**  
ART. A00175

**ELEVATION 63**  
ART. A00188

**ADA LIFT 34**  
ART. A00492

|                   |      |      |      |
|-------------------|------|------|------|
| Height Max., cm   | 153  | 300  | 340  |
| Head diameter, cm | 5    | 6    | 5    |
| Thread            | 1/8" | 1/8" | 1/8" |

## ELEVATION 16B / 63 / LIFT 34



ELEVATION 16B  
ART. A00175

## Elevating tripod

Elevating tripods ADA Elevation 19 and 30 are made of strong aluminium form and metal. They are designed for mounting different kinds of instrument with thread 5/8". Models have minimum and maximum height adjustment and differ in weight.

ADA LIFT 300 - is a high, stable classic tripod with a telescopic part (column), with replaceable adapters for 1/4 and 5/8" thread. The column is equipped with a rack-and-pinion mechanism for smooth lifting in the range of 85 cm. Fixation of telescopic legs with the clips. Screw-type rubber parts for choosing the type of support - rubber or metal tip. An adapter with 1/4 or 5/8 inch thread can be installed on the tripod head.



**ADA LIFT 300**  
ART. A00676

**ELEVATION 19**  
ART. A00186

**ELEVATION 30**  
ART. A00187

|                   |            |      |      |
|-------------------|------------|------|------|
| Height Max., cm   | 340        | 185  | 300  |
| Head diameter, cm | 5          | 5,5  | 14,5 |
| Thread            | 5/8", 1/4" | 5/8" | 5/8" |

## ELEVATION 19 / 30 / LIFT 300



LIFT 300  
ART. A00676

# LIGHT / LIGHT S



LIGHT ART. A00179

## Surveying tripods


Surveying tripods of ADA Light series are light and strong aluminium tripods for installation of line lasers, theodolites and other tools with the weight up to 3 kg.

There are two models in the series ADA light. They have different heads, types of the attachment of legs:

- Light - flat head, clips, shoulder strap;
- 
- Light S - flat head, screws, shoulder strap.

|                   | LIGHT<br>ART. A00179 | LIGHT S<br>ART. A00177 |
|-------------------|----------------------|------------------------|
| Height Max., cm   | 101-173              | 101-173                |
| Head diameter, cm | 125                  | 125                    |
| Thread            | 5/8"                 | 5/8"                   |

# STAFF 3, 4, 5



STAFF 3  
ART. A00141

STAFF 4  
ART. A00142

STAFF 5  
ART. A00143

## Leveling staff

Leveling staff ADA Staff 3, 4, 5 - is a telescopic staff that is made of high-quality aluminium alloy.

«E» scale from the front side is a red and black color. Millimeter scale from the backside. Millimeter scale starts from the bottom part of the staff. The scale is made on all sections along the entire length of the staff.

ADA Staff 3 - Length 3m, ADA Staff 4 - Length 4m, ADA Staff 5 - Length 5m.

# STRONG S



ART. A00178

## Surveying tripods

Surveying tripod ADA Strong S - is an aluminium strong tripod for the installation of laser levels, theodolites, total stations and other tools with the weight up to 9 kg.

Tripod has a flat head and screws.

|                   |      |
|-------------------|------|
| Height Max., cm   | 168  |
| Head diameter, mm | 160  |
| Head diameter, mm | 5/8" |





